

10/527170

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)


PCT

(10) International Publication Number
WO 2004/024553 A1

- (51) International Patent Classification⁷: **B63B 21/04**, (74) Agents: EISEN, Mark, B. et al.; Dimock Stratton Clarizio LLP, 20 Queen St. W., Suite 3202, Box 102, Toronto, Ontario M5H 3R3 (CA).
B66D 1/50
- (21) International Application Number: PCT/CA2003/000362
- (22) International Filing Date: 18 March 2003 (18.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2,397,926 11 September 2002 (11.09.2002) CA
- (71) Applicants and
(72) Inventors: **GORDON, Leslea, C.** [CA/CA]; 2269 Lakeshore Blvd. West, Suite 2708, Toronto, Ontario M8V 3X6 (CA). **KNIGHT, Darrel, C.** [CA/CA]; 2269 Lakeshore Blvd. West, Suite 2708, Toronto, Ontario M8V 3X6 (CA). **HANNA, Farhat** [CA/CA]; 31 Poplar Street, Leamington, Ontario N8H 3L3 (CA).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: RETRACTABLE MOORING LINE DEVICE



(57) Abstract: A retractable mooring line device comprising a reel for storing and paying off a mooring line (2), having side walls (22, 24) each comprising a series of notches (60) for receiving a releasable latch (54). A latch simultaneously engages between notches in both side walls (22, 24) at a substantially right angle to provide a secure, positive locking engagement between the latch and the reel while permitting the latch (54) to be released under the application of relatively little force. In the preferred embodiment the latch may be actuated by a user's hand or foot and is biased toward the reel by a spring (70) which bears against the housing (18). The mechanism can be exposed for maintenance or repair simply by removal of the gunnel plate (16) and reinstallation of the gunnel plate does not require special loading of the latch spring.

WO 2004/024553 A1



Published:

- with international search report
- with amended claims and statement

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.